



TRIBUNOL Polardiol G 12++

Polardiol G 12++ is a practice-proven, blue/green coloured coolant concentrate based on corrosion inhibited monoethylene glycols.

DESCRIPTION

Polardiol G 12++ is used in modern, water-cooled engines in which aluminium parts are also used. It contains no nitrite, amine or phosphate and protects safe against rust, freezing or overheating in summer temperatures. This product is not suitable for protecting drinking water pipes against frost or corrosion!

BENEFITS

- long and excellent corrosion protection
- improved heat transfer
- suitable for mixed fleets
- provides long-term protection for all materials used on the motor,
- especially for aluminium and iron alloys. A change of coolant is recommended after 5 years at the earliest.

Recommended and tested in units for which the following specifications and filling instructions are required

MB 325.3
Ford WSS M97B44-D
GM 6277M
MAN 324 Typ SNF
VW TL 774F(G12++)

ATTENTION:

This product is not suitable for protecting drinking water pipes against frost or corrosion!

Miscibility and compatibility

Polardiol G12++ is miscible with most coolants based on ethylene glycol. For an optimal corrosion protection effect and to prevent sludge formation, the unmixed application of recommended. Softened water should preferably be used to prepare aqueous solutions.

Einsatz nach Vorschriften der Motorenhersteller
Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen
Stand: Januar 2020

Rev. 11.01.2020

TRIBUTECH GmbH
Windhauser Weg 2 - 41366 Schwalmtal