



TRIBUNOL ATF 200

Tribunol ATF 200 is a special gear oil for use in automatic transmissions and the systematic further development of gear oils according to Type A Suffix A, as well as Dexron B.

DESCRIPTION

It is characterized by extremely high oxidation stability and highly effective high-pressure additives. This gives Tribunol ATF 200 excellent load carrying capacity, high ageing and excellent wear protection. It hardly forms any foam, even under difficult conditions, but is nevertheless absolutely neutral towards sealing materials. Tribunol ATF 200 can be used wherever gear oils are specified according to Dexron II, Dexron B or TASA..

BENEFITS

- high thermal stability
- high shifting comfort, even at very low Temperatures
- original viscosity-temperature behaviour even with long changing intervals
- very high wear protection
- neutral to sealing materials

Recommended and tested in units for which the following specifications and filling instructions are required

GM Dexron II D

Ford Mercon
 MB 236.1
 MAN 339 Typ Z1
 Voith 55.6335 (G607)
 TASA
 Allison C-4
 Cat TO-2
 ZF TE-ML 02F, 03D, 04D, 09, 11B, 14A,17E

TECHNICAL DATA

| Properties | Method | Unit | Value |
|-----------------|--------------|--------------------|-------|
| Density 15 °C | DIN 51757 | g/ ml | 0,86 |
| Viscosity 40°C | DIN 51562 | mm ² /s | 42 |
| Viscosity 100°C | DIN 51562 | mm ² /s | 7,8 |
| Viscosity Index | DIN 2909 | - | 158 |
| Flash Point | DIN ISO 2592 | °C | 185 |
| Pourpoint | DIN ISO 3016 | °C | -45 |

Einsatz nach Vorschriften der Motorenhersteller

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen

Stand: Dezember 2019

Rev. 11.01.2020

TRIBUTECH GmbH
 Windhauser Weg 2 - 41366 Schwalmtal