



TRIBUNOL ATF 300

Tribunol ATF 300 is a special gear oil for use in automatic transmissions and the result of ongoing development according to Dexron II G.

DESCRIPTION

It has excellent oxidation stability and highly effective high-pressure additives. Therefore Tribunol ATF 300 excellent load bearing capacity, extremely high ageing and wear protection and is designed for longest change intervals (up to "fill-for-life" regulation). It does not form foams, even under the most difficult conditions, but is nevertheless absolutely neutral towards sealing materials. Tribunol ATF 300 can be used wherever gear oils are specified according to the Dexron III G, Dexron II E, or Dexron II D specification.

BENEFITS

- high thermal resistance
- high shifting comfort, even at very low Temperatures
- rationalisation of the variety of types to one grade
- very high wear protection
- neutral to sealing materials

Recommended and tested in units for which the following specifications and filling instructions are required

GM Dexron III H

Ford Mercon

MB 236.5, MB 236.1

Cat TO-2

Voith 55.6335 (G607)

TASA

Allison C-4

Volvo 97341

ZF TE-ML 02F, 03D, 04D, 09, 11B, 14A, 14B, 17C

TECHNISCHE DATEN

Properties	Method	Unit	Value
Density 15 °C	DIN 51757	g/ ml	0,86
Viscosity 40°C	DIN 51562	mm ² /s	39
Viscosity 100°C	DIN 51562	mm ² /s	7,5
Viscosity Index	DIN 2909	-	163
Flash Point	DIN ISO 2592	°C	185
Pourpoint	DIN ISO 3016	°C	-48