



## TRIBUNOL C-3 5W-40

Tribunol C-3 5W-40 is a advanced car engine oil, which has been specially designed for modern high-performance engines of the VW and Audi brands. However, it can also be used in models of various other manufacturers who have a corresponding classification.

### DESCRIPTION

It offers excellent, field-proven protection against wear, deposits and sedimentation. Tribunol C-3 5W-40 has been developed to improve the fuel economy of vehicles such as oil spillage, oil spillages, etc. more efficient and protect compressor components. It optimizes the service life of exhaust aftertreatment systems such as catalytic converters or soot particle filters.

### BENEFITS

- excellent wear protection
- optimum oil pressure
- minimal friction and evaporation loss
- optimal engine cleanliness due to intensive cleaning effect
- reduction of emissions
- fuel saving

### Recommended and tested in units for which the following specifications and filling instructions are required

SAE 5W-40  
ACEA C3  
API SN/CF

MB 229.51, MB 229.31, MB 226.5  
VW 505.00, VW 505.01, VW 502.00  
Porsche A40  
Ford WSS-M2C917-A  
BMW Longlife-04  
Renault RN0700, Renault RN0710  
Fiat 9.55535-S2  
GM DX2 / Opel DX2  
Für alle Opel Motoren ab Baujahr 2010  
rückwärtskompatibel mit GM-LL-A-025 als auch GM-LL-B-025 (Baujahre vor 2010)

### TECHNICAL DATA

Properties	Method	Value	Unit
Density 15°C	DIN 51757	g/ ml	0,85
Viscosity 40°C	DIN 51562	mm <sup>2</sup> /s	76
Viscosity 100°C	DIN 51562	mm <sup>2</sup> /s	14
Viscosity index	DIN 2909	-	170
Flash point	DIN ISO 2592	°C	218
Pourpoint	DIN ISO 3016	°C	-38

Use in accordance with engine manufacturer's instructions  
All characteristic data are average values and are subject to production-related fluctuations  
Status: January 2020

Rev. 11.01.2020

TRIBUTECH GmbH  
Windhauser Weg 2 - 41366 Schwalmtal