

TRIBUNOL C-4 5W-30

Tribunol C-4 5W-30 is a top class passenger car engine oil which has been specially designed for the most modern high performance Renault engines; however, it can also be used in models of the Mercedes Benz brand which have an appropriate ACEA classification.

DESCRIPTION

It offers excellent protection against wear, deposits and abrasion, while at the same time providing the best possible protection for particle or oxidation filters. Tribunol C4 5W-30 was developed to improve the fuel economy of vehicles in the long term and to protect turbocharger components so that the boost pressure remains optimal in the long term, even with vulnerable systems. It optimises the service life of exhaust aftertreatment systems such as catalytic converters or soot particle filters and can be used for extended maintenance intervals

BENEFITS

- excellent wear protection
- optimization of the service life of exhaust aftertreatment systems
- low oil consumption

- · reduction of exhaust emissions
- high operational reliability
- reduction of fuel consumption

Recommended and tested in units for which the following specifications and filling instructions are required

SAE 5W-20 ACEA C5 API SN Chrysler MS-6395 Ford WSS-M2C948-A Ford WSS-M2C948-B Ford WSS-M2C925-A Ford WSS-M2C925-B

TECHNICAL DATa

1 E G I I I I G I E G I I I I I I I I I I				
Properties Density 15°C	Method DIN 51757	Value g/ ml	Unit 0,851	
Viscosity 40°C	DIN 51562	mm²/s	42,2	
Viscosity 100°C	DIN 51562	mm²/s	7,9	
Viscosity index	DIN 2909	-	161	
Flash point	DIN ISO 2592	°C	232	
Pourpoint	DIN ISO 3016	°C	-42	

Use in accordance with engine manufacturer's instructions

All characteristic data are average values and are subject to production-related fluctuations

Status: December 2019

Rev. 11.01.2020