



TRIBUNOL CGLP

Tribunol CGLP are tried and tested products suitable for slideway and guideway systems, but also for drive chains.

DESCRIPTION

Good corrosion properties and excellent adhesion reliably prevent rust stains. In addition, the lubricating film remains constant even in the presence of aqueous metalworking media (such as drilling, cutting and grinding emulsions) and continued rinsing is reliably prevented.

BENEFITS

- strong adhesion
- good corrosion-protection properties
- no rust and stain formation
- resistant to aqueous metalworking media
- high temperature stability

Recommended and tested when the following specifications and filling instructions are required

DIN 51517 Part 3 (with adhesive additive)

TECHNICAL DATA

Properties	Method	Value	ISO 68	ISO 150	ISO 220
Density 15°C	DIN 51757	g/ ml	0,878	0,885	0,887
Viscosity 40°C	DIN 51562	mm ² /s	68	150	220
Viscosity 100°C	DIN 51562	mm ² /s	9	15	19
Viscosity index	DIN 2909	-	100	100	98
Flash point	DIN ISO 2592	°C	225	240	246
Pourpoint	DIN ISO 3016	°C	-14	-12	-10

Use in accordance with engine manufacturer's instructions
 All key data are average values and are subject to production-related fluctuations Status: January 2020

Rev. 11.01.2020

TRIBUTECH GmbH
 Windhauser Weg 2 - 41366 Schwalmtal