



## TRIBUNOL Eurotruck LA 5W-30

Tribunol Eurotruck LA 5W-30 is a premium class commercial vehicle engine oil, specially developed for the latest high-performance engines.

### DESCRIPTION

Due to optimal oxidation and ageing stability it offers highest fuel savings, high protection against wear, deposits and extends the replacement interval outstandingly. Tribunol Eurotruck LA 5W-30 is designed to significantly improve the fuel economy of vehicles, to protect turbocharger components as well as to provide rationalized applications.

### BENEFITS

- most modern "Low SAPS" - additive technology
- Suitable for longest oil change intervals
- excellent wear protection even under high load
- Fuel saving
- Best protection for modern exhaust aftertreatment systems
- high resistance to oxidation and ageing

### Recommended and tested in units for which the following specifications and filling instructions are required

SAE 5W-30  
ACEA E7/E6/E9  
API CI-4

MAN M3477  
MAN M3277, MAN M3275, MAN M3271-1  
MB 228.51  
Volvo VDS-3  
Mack EO-N, Mack EO-M  
Caterpillar ECF-1a  
Cummins CES 20077, Cummins CES 20076  
MTU DDC Type 3.1  
Renault RDL-2, Renault RXD, Renault RGD  
Scania LA  
DAF

### TECHNICAL DATA

Properties	Method	Value	Unit
Density 15°C	DIN 51757	g/ ml	0,865
Viscosity 40°C	DIN 51562	mm <sup>2</sup> /s	69,9
Viscosity 100°C	DIN 51562	mm <sup>2</sup> /s	11,1
Viscosity index	DIN 2909	-	160
Flash point	DIN ISO 2592	°C	218
Pourpoint	DIN ISO 3016	°C	-35

Use in accordance with engine manufacturer's instructions

All key data are average values and are subject to production-related fluctuations Status: January 2020

Rev. 11.01.2020

TRIBUTECH GmbH  
Windhauser Weg 2 - 41366 Schwalmtal