



TRIBUNOL F 5W-30

Tribunol F 5W-30 leading car engine oil, which has been specially designed for the latest high-performance Ford engines. It can also be used in models of Renault, Jaguar and Chrysler, which have a corresponding classification.

BESCHREIBUNG

It offers excellent protection against wear and deposits. Tribunol F 5W-30 was developed to improve the fuel economy of vehicles with regard to oil change intervals and oil losses and to protect turbocharger components.

BENEFITS

- excellent wear protection
- high operational reliability
- low oil consumption
- optimum engine cleanliness
- Reduction of fuel consumption

Recommended and tested in units for which the following specifications and filling instructions are required

SAE 5W-30
ACEA A5/B5
API SL/CF

Ford WSS-M2C913-D
Ford WSS-M2C913-C
Ford WSS-M2C913-A
Ford WSS-M2C913-B
Renault RN0700
Iveco 18-1811
Jaguar

TECHNICAL DATA

Properties	Method	Value	Unit
Density 15°C	DIN 51757	g/ ml	0,86
Viscosity 40°C	DIN 51562	mm ² /s	70
Viscosity 100°C	DIN 51562	mm ² /s	11
Viscosity index	DIN 2909	-	148
Flash point	DIN ISO 2592	°C	215
Pourpoint	DIN ISO 3016	°C	-40

Use in accordance with engine manufacturer's instructions

All key data are average values and are subject to production-related fluctuations Status: January 2020