



## TRIBUNOL GM 5W-30

Tribunol GM 5W-30 is a premium class passenger car engine oil, which has been specially designed for the most modern high-performance engines of the Opel Automobile GmbH (formerly GMC) brand; however, it can also be used in models of various other manufacturers that have a corresponding classification.

### DESCRIPTION

It offers excellent, field-proven protection against wear, deposits and siltation.

Tribunol GM 5W-30 has been developed to improve the fuel economy of vehicles with regard to oil change intervals as well as oil losses, and protect turbocharger components. It optimizes the service life of exhaust aftertreatment systems such as catalytic converters or soot particle filters and can be used for extended maintenance intervals.

### BENEFITS

- excellent wear protection
- optimum oil pressure
- high operating safety
- optimal engine cleanliness due to intensive cleaning effect
- low oil consumption
- Fuel saving

### Recommended and tested in units for which the following specifications and filling instructions are required:

SAE 5W-30  
ACEA C3  
API SN/CF

BMW Longlife-04  
MB 229.52, MB 229.51, MB 229.31  
VW 505.00, VW 505.01, VW 502.00  
Fiat 9.55535-S3  
Ford WSS-M2C917-A  
PSA B71 2297  
GM DX2 / Opel DX2  
Für alle Opel-Motoren ab Baujahr 2010  
rückwärtskompatibel mit GM-LL-A-025 als  
auch GM-LL-B-025 ( Baujahr vor 2010 )

### TECHNICAL DATA

Properties	Method	Value	Unit
Density 15°C	DIN 51757	g/ ml	0,855
Viscosity 40°C	DIN 51562	mm <sup>2</sup> /s	70
Viscosity 100°C	DIN 51562	mm <sup>2</sup> /s	12
Viscosity index	DIN 2909	-	165
Flash point	DIN ISO 2592	°C	212
Pourpoint	DIN ISO 3016	°C	-35

Use in accordance with the engine manufacturer's instructions

All characteristic data are average values and are subject to production-related fluctuations Status: December 2019

Rev. 11.01.2020

TRIBUTECH GmbH  
Windhauser Weg 2 - 41366 Schwalmtal