



TRIBUNOL Gatterhaftöl

Tribunol Gate Adhesion Oil is a modern, field-tested product, especially for use on saw frames.

DESCRIPTION

It is used where good lubricating properties as well as optimum adhesion with very good temperature behaviour are required. In addition to vertical guides and sliding surfaces, Tribunol Gatterhaft Oil also lubricates the slideway of the carriage reliably, even at very low feed rates.

BENEFITS

- strong adhesion
- extended lubrication intervals
- good corrosion-protection properties
- resistant to aqueous metalworking fluids

TECHNICAL DATA

| Eigenschaft | Methode | Einheit | ISO 68 | ISO 100 | ISO 150 | ISO 220 | ISO 320 |
|----------------------|--------------|--------------------|--------|---------|---------|---------|---------|
| Dichte bei 15 °C | DIN 51757 | g/ ml | 0,878 | 0,88 | 0,885 | 0,887 | 0,887 |
| Viskosität bei 40°C | DIN 51562 | mm ² /s | 68 | 100 | 150 | 220 | 320 |
| Viskosität bei 100°C | DIN 51562 | mm ² /s | 9 | 11,5 | 15 | 19 | 24 |
| Viskositätsindex | DIN 2909 | - | 100 | 100 | 100 | 98 | 95 |
| Flammpunkt | DIN ISO 2592 | °C | 225 | 235 | 240 | 245 | 250 |
| Pourpoint | DIN ISO 3016 | °C | -12 | -12 | -12 | -10 | -10 |

Use in accordance with engine manufacturer's instructions
 All key data are average values and are subject to production-related fluctuations Status: January 2020

Rev. 11.01.2020

TRIBUTECH GmbH
 Windhauser Weg 2 - 41366 Schwalmtal