



TRIBUNOL Gear HYP 85W-140 GL5

Tribunol Gear HYP 85W-140 GL5 GL5 is a transmission oil specially developed for heavy-duty gearboxes.

DESCRIPTION

It offers extremely low-wear lubrication and maximum pressure absorption capacity. Tribunol Gear HYP 80W-90 GL5 does not form foam even under heavy duty conditions, but is absolutely neutral against various sealing materials. It can be used wherever gear oils of the API specification GL5 of SAE class 85W-140 are required.

BENEFITS

- well adhering and pressure resistant lubricating film
- excellent oxidation stability
- good viscosity-temperature behaviour
- wear-resistant
- no foam formation
- neutral to sealing materials

Recommended and tested in units for which the following specifications and filling instructions are required

SAE 85W-140
API GL5

Scania STO 1.0
MB 235.6, MB 235.0
Ford WSS-M2C9002-AA
DAF
MIL-L-2105 D
MIL-L-2105 C
ZF TE ML 01, 05A, 07A, 12E, 16C-D, 17B,
21A

TECHNICAL DATA

Properties	Method	Unit	Value
Density 15 °C	DIN 51757	g/ ml	0,893
Viscosity 40°C	DIN 51562	mm ² /s	360
Viscosity 100°C	DIN 51562	mm ² /s	28
Viscosity Index	DIN 21409	-	105
Flash Point	DIN ISO 2592	°C	245
Pourpoint	DIN ISO 3016	°C	-20

Use in accordance with engine manufacturer's instructions

All key data are average values and are subject to production-related fluctuations Status: January 2020

Rev. 11.01.2020

TRIBUTECH GmbH
Windhauser Weg 2 - 41366 Schwalmtal