



TRIBUNOL Gear HYP 85W-90 GL5

Tribunol Gear HYP 85W-90 GL5 is a gear oil, especially developed for extremely stressed axle gears.

DESCRIPTION

It offers extremely low-wear lubrication and maximum pressure absorption capacity. Tribunol Gear HYP 85W-90 GL5 does not form foam even under heavy duty conditions, but is nevertheless absolutely neutral towards various sealing materials. It can be used wherever gear oils of the API specification GL5 of SAE class 85W-90 are required.

BENEFITS

- well adhering and pressure resistant lubricating film
- excellent oxidation stability
- good viscosity-temperature behaviour
- wear-resistant
- no foam formation
- neutral to sealing materials

Recommended and tested in units for which the following specifications and filling instructions are required:

SAE 85W-90
API GL5

MAN 342 M2, MAN 342 M1
API GL5 MB 235.0, 235.6
Ford M2C9002-AA
Volvo 97310
DAF
MIL-L-2105 D
MIL-L-2105 C

TECNICAL DATA

Properties	Method	Value	Unit
Density 15°C	DIN 51757	g/ ml	0,886
Viscosity 40°C	DIN 51562	mm ² /s	145
Viscosity 100°C	DIN 51562	mm ² /s	15
Viscosity index	DIN 21409	-	108
Flash point	DIN ISO 2592	°C	220
Pourpoint	DIN ISO 3016	°C	-21

Use in accordance with the engine manufacturer's instructions

All characteristic data are average values and are subject to production-related fluctuations: Januar 2020

Rev. 11.01.2020

TRIBUTECH GmbH
Windhauser Weg 2 - 41366 Schwalmtal