



## TRIBUNOL HP 10W-60

Tribunol HP 10W-60 is a low-friction engine oil for use in modern models of various manufacturers who provide for a corresponding classification. It is characterised by a very good viscosity-temperature behaviour, even under unfavourable conditions

### DESCRIPTION

TRIBUNOL HP 10W-60 is an engine oil, especially for all-season use. The modern additive technology counteracts friction losses as well as corrosion. Its formulation optimises the oil pressure, tends to lower evaporation losses and thus contributes to operational safety

### BENEFITS

- high wear protection
- excellent detergent and dispersant properties
- long service life due to high oxidation stability
- very good viscosity-temperature behaviour
- low vaporisation inclination
- catalytic converter suitable

**Recommended and tested in units for which the following specifications and filling instructions are required:**

SAE 10W-60  
ACEA A3/B4  
API SL

### TECHNICAL DATA

Properties	Method	Value	Unit
Density 15°C	DIN 51757	g/ ml	0,86
Viscosity 40°C	DIN 51562	mm <sup>2</sup> /s	85
Viscosity 100°C	DIN 51562	mm <sup>2</sup> /s	26
Viscosity index	DIN 2909	-	170
Flash point	DIN ISO 2592	°C	220
Pourpoint	DIN ISO 3016	°C	-30

Use in accordance with the engine manufacturer's instructions

All characteristic data are average values and are subject to production-related fluctuations Status: December 2019

Rev. 11.01.2020

**TRIBUTECH GmbH**  
Windhauser Weg 2 - 41366 Schwalmtal