



## TRIBUNOL Hyd HLP-B 46

Tribunol Hyd HLP-B 46 is an easily biodegradable hydraulic oil based on vegetable raw materials.

### DESCRIPTION

It has excellent properties in wear protection, oxidation stability, corrosion, low temperature and EP behaviour.

Tribunol Hyd HLP-B 46 meets all minimum technical requirements according to VDMA 24568 / ISO 15380; degradability according to OECD 301 B is given.

Tribunol Hyd HLP-B 46 is particularly suitable for use in areas where there is a risk of leaking hydraulic fluid into the ground or waste water. can reach, such as

- Sewage treatment plants
- Dredgers and dredgers
- Lock hydraulics and river weirs
- Hydraulic power units in forest and field
- Earthmoving machinery in water
- Forestry machinery

### TECHNICAL DATA

Properties	Method	Value	Unit
Density 15°C	DIN 51757	g/ ml	0,923
Viscosity 40°C	DIN 51562	mm <sup>2</sup> /s	45,7
Viscosity 100°C	DIN 51562	mm <sup>2</sup> /s	8,5
Viscosity index	DIN 2909	-	190
Flash point	DIN ISO 2592	°C	>300
Pourpoint	DIN ISO 3016	°C	-28

Einsatz nach Vorschriften der Motorenhersteller  
 Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen  
 Stand: Januar 2020

Rev. 11.01.2020

**TRIBUTECH GmbH**  
 Windhauser Weg 2 - 41366 Schwalmtal