



TRIBUNOL Megatruck 10W-40

Tribunol Megatruck 10W-40 is a commercial vehicle engine oil, specially developed for modern commercial vehicle engines.

DESCRIPTION

Thanks to its very good oxidation and ageing stability, it also offers fuel savings, proven protection against wear, deposits and silting and extends the replacement interval.

Tribunol Megatruck 10W-40 has been designed to positively contribute to the fuel economy of vehicles without exhaust gas after-treatment, to protect turbocharger components and to rationalise applications to unite.

BENEFITS

- excellent wear protection
- excellent viscosity-temperature behaviour
- excellent cold start behaviour (wear reducing)
- high operating safety
- optimum engine cleanliness

Recommended and tested in units for which the following specifications and filling instructions are required:

SAE 10W-40
ACEA E4/E7
API CI-4
Global DHD-1

MAN M3277 / MAN M3377
MB 228.5
Renault Trucks RXD
Renault RLD-2
Volvo VDS-3
MTU DDC Type 3
Cummins CES 20078 / Cummins CES 20077
Detroit Diesel DDC 93K215
Mack EO-N, Mack EO-M
Scania LDF-2, Scania LDF
DAF
Caterpillar ECF 2

TECHNICAL DATA

Properties	Method	Value	Unit
Density 15°C	DIN 51757	g/ ml	0,86
Viscosity 40°C	DIN 51562	mm ² /s	92
Viscosity 100°C	DIN 51562	mm ² /s	14
Viscosity index	DIN 2909	-	156
Flash point	DIN ISO 2592	°C	218
Pourpoint	DIN ISO 3016	°C	-34

Einsatz nach Vorschriften der Motorenhersteller Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen
Stand: Januar 2020

Rev. 11.01.2020

TRIBUTECH GmbH
Windhauser Weg 2 - 41366 Schwalmtal