



TRIBUNOL Supergear 75W-80 GL4

Tribunol Supergear 75W-80 GL4 is a transmission oil of the premium class, especially for transaxle systems, manual and transfer cases, but also for highly loaded, synchronised and non-synchronised manual transmissions and axle drives

DESCRIPTION

Due to its excellent oxidation and ageing stability, it also offers outstanding protection against wear, deposits and siltation. Tribunol Supergear 75W-80 GL4 thus achieves the longest change intervals (up to "fill-for-life" regulation), with the highest power density at the same time. Tribunol Supergear 75W-80 GL4 is recommended for 5- and 6-speed manual transmissions of Volkswagen, Seat, Skoda and Audi.

Recommended and tested in units for which the following specifications and filling instructions are required:

SAE 75W-80
API GL4

Alpha Romeo
BMW, Mini
PSA (Citroen, Peugeot)
Renault, Dacia
VW, Seat, Skoda
Fiat
Honda
Volvo
MB, Smart
Alpha Romeo
BMW, Mini
Wenn die Viskosität 75W-80 und
Performance API GL4 gefordert ist.
MB 235.29
MAN 341 Z4
DAF
Eaton
Voith Retarder
Volvo 97307

TECHNICAL DATA

Properties	Method	Value	Unit
Density 15°C	DIN 51757	g/ ml	0,86
Viscosity 40°C	DIN 51562	mm ² /s	40
Viscosity 100°C	DIN 51562	mm ² /s	8
Viscosity index	DIN 2909	-	150
Flash point	DIN ISO 2592	°C	223
Pourpoint	DIN ISO 3016	°C	-60

Einsatz nach Vorschriften der Motorenhersteller

Alle Kenndaten sind Mittelwerte und unterliegen produktionsbedingten Schwankungen Stand: Januar 2020

Rev. 11.01.2020

TRIBUTECH GmbH
Windhauser Weg 2 - 41366 Schwalmtal