



TRIBUNOL UTTO 10W-30

Tribunol UTTO 10W-30 is a multifunctional oil, especially for the agricultural use in agricultural tractors and other machines.

DESCRIPTION

In addition to excellent characteristics, friction coefficients and wear protection properties, it has a strong extended temperature range. Tribunol UTTO 10W-30 has been designed to meet the making a positive contribution to the fuel economy of vehicles, transmission components as well as the rationalizing application. The Applications include transmissions, rear axles, submerged brakes of tractors and forklift trucks, moving hydraulic systems (e.g. cranes), branch couplings, Power steering systems as well as axles of hypoid tractor clutches according to API GL 4.

BENEFITS

- well adhering and pressure resistant lubricating film
- excellent oxidation stability
- good viscosity-temperature behaviour
- wear-resistant
- no foam formation
- **outstanding performance**

Recommended and tested in units for which the following specifications and filling instructions are required

SAE 10W-30
API GL4
DIN 51524 Part 3

Ford WSS-M2C134-D, Ford WSS-M2C48-C2
John Deere JDM 20 C
CNH MAT 3525, CNH MAT 3526
Massey Ferguson CMS M 1143, CMS M 1145
Ford WSS-M2C134-D, Ford WSS-M2C48-C2
Allison C-4, Caterpillar TO-2
Komatsu B 06-0002
New Holland NH 410B, NH 420A
Volvo WB 101, Volvo 97303
Sperry Vickers / Eaton I-280 S
ZF TE ML 03E, 05E, 06A*, B*, C*, 07B

TECHNICAL DATA

Properties	Method	Unit	Value
Density 15 °C	DIN 51757	g/ ml	0,878
Viscosity 40°C	DIN 51562	mm ² /s	62
Viscosity 100°C	DIN 51562	mm ² /s	10,5
Viscosity Index	DIN 2909	-	160
Flash Point	DIN ISO 2592	°C	230
Pourpoint	DIN ISO 3016	°C	-39

Use in accordance with engine manufacturer's instructions

All key data are average values and are subject to production-related fluctuations Status: January 2020

Rev. 11.01.2020

TRIBUTECH GmbH
Windhauser Weg 2 - 41366 Schwalmtal