



TRIBUNOL UTTO 10W-40

Tribunol UTTO 10W-40 is a multifunctional oil, especially for agricultural use in agricultural tractors and other working machines.

DESCRIPTION

In addition to excellent friction coefficients and wear protection properties, it has a greatly extended temperature range. Tribunol UTTO 10W-30 has been designed to reduce the consumption of vehicles, protect transmission components, as well as to combine the rationalizing application. It is used in transmissions, rear axles, submerged brakes of tractors and forklifts, moving hydraulic systems (e.g. cranes), branch clutches, power steering systems and axles of hypoid tractor clutches according to API GL 4. The SAE 10W-30 viscosity class allows year-round supply and ensures very good cold start performance of the engines and excellent response of the hydraulic systems.

Recommended and tested in units for which the following specifications and filling instructions are required:

SAE 10W-40
DIN 51524 Teil 3
API GL4

Ford WSS-M2C134-D, Ford WSS-M2C48-C2
John Deere JDM 20 C
CNH MAT 3525, CNH MAT 3526
Massey Ferguson CMS M 1143
Massey Ferguson CMS M 1145
Allison C-4, Caterpillar TO-2
Komatsu B 06-0002
Sperry Vickers / Eaton I-280 S
New Holland 410B, 420A
Volvo WB 101, Volvo 97303
Fendt KDM17/2012
ZF TE ML 03E, 05E, 06A*, B*, C*, 07B
*exklusive aktueller Vorgabe aus KRL-Test

TECHNICAL DATA

Properties	Method	Value	Unit
Density 15°C	DIN 51757	g/ ml	0,878
Viscosity 40°C	DIN 51562	mm ² /s	87
Viscosity 100°C	DIN 51562	mm ² /s	13,5
Viscosity index	DIN 2909	-	160
Flash point	DIN ISO 2592	°C	225
Pourpoint	DIN ISO 3016	°C	-30

Use in accordance with the engine manufacturer's instructions
All characteristic data are average values and are subject to production-related fluctuations
Status: December 2019